




CHECK
PRICES

login to the
Partners Section



SILVERSTEP 2,0mm EPE foam + PE FOIL

Recommended as an underlay for:

laminated flooring, engineered wooden flooring, vinyl flooring

Package content: 1 roll = 25m²

Roll size (w x l): 1,1 x 22,8m

Thickness: 2,00mm +/- 0,3mm

Density: 25kg/m³ +/- 1kg

Ecology: does not pollute, toxicly harmless

Recycling: waste disposal with energy renewal

Waste disposal: with normal household waste

Flamable class: B3

Benefits:

This underlay protects floors with quality moisture protection while offering basic sound insulation

Pre-attached moisture barrier helps protect floor from moisture damage

Suitable for underfloor heating

Self-leveling

Easy to install with attached overlapping lip and tape

Properties	COMBI UNDERLAYER 2,0mm	
Step insulation (inside the room)	●●●	18 db(A)
Step insulation (into do room)	●●	8%
Heat resistance	●	0,05 m ² K/W
Underfloor heating	●●●	YES
Protection against moisture	●●●	Vapourtight layer
Levelling uneven ground	●●	
Mechanical stress	●●	
Longevity	●●	

●●●●● excellent
●●●●● very good
●●●● good
●●● satisfactory
● sufficient

Material:

PE foil - 60 microns, PE overlaps by 10cm and contains a self-adhesive strip

Storage:

1 year, must be protected from direct sunlight and climate conditions